



- **개요** 8 * 10/100/1000Base-T PoE ports (Power/Data)
+ 2 * 1G SFP Slot (Data)

- **특징** 광 포트 25-28포트 : 1G 지원
AC input : 100-240V 50-60HZ
0 ~ +50°C operation temperature

제품사양

고정포트	8 * 10/100/1000Base-T PoE ports (Power/Data), 2 * 1G uplink SFP slot ports (Data), AC input : 100-240V 50-60HZ
이더넷 포트	Port 1-8 support 10/100/1000Base-T, auto-sensing, Full/half duplex MDI/MDI-X self-adaption
트위스트 프로토콜	10BASE-T : Cat3, 4, 5 UTP(≤100 meter), 100BASE-TX : Cat5 or later UTP(≤100 meter) 1000BASE-T : Cat5e or later UTP(≤100 meter)
POE 포트	Port 1 to port 8
PoE Management	PoE working status, Delay start of power supply, PoE output priority configuration Scheduling of PoE operation and time, Total power limit of PoE power supply PoE output power allocation, off& af & at
스위치 용량	20Gbps
Flash memory	32M Byte
DDRIII capacity	128M Byte
버퍼 메모리	4.1M
MAC	8K
정보 프레임	9K
입력전압	AC input : 100-240V 50-60HZ
소비전력	POE full load <150W
Operation TEMP / Humidity	0 ~ +50°C, 10%~90% RH Non condensing
Storage TEMP / Humidity	-40 ~ +70°C, 10%~90% RH Non condensing
치수 (L x H x D mm)	320X230X43.6 mm
설치	Desktop