

- **개요** 24 \* 10/100/1000Base-T PoE ports (Power/Data)  
+ 4 \* 10G SFP+ Slot (Data)



- **특징** 광 포트 25-28포트 : 10G 지원  
AC input : 100-240V 50-60HZ  
0 ~ +50°C operation temperature

## 제품사양

고정포트	24 * 10/100/1000Base-T PoE ports (Power/Data), 4 * 10G uplink SFP+ slot ports (Data), AC input : 100-240V 50-60HZ
이더넷 포트	Port 1-24 support 10/100/1000Base-T, auto-sensing, Full/half duplex MDI/MDI-X self-adaption
트위스트 프로토콜	10BASE-T : Cat3, 4, 5 UTP(≤100 meter), 100BASE-TX : Cat5 or later UTP(≤100 meter) 1000BASE-T : Cat5e or later UTP(≤100 meter)
POE 포트	Port 1 to port 24
PoE Management	PoE working status, Delay start of power supply, PoE output priority configuration Scheduling of PoE operation and time, Total power limit of PoE power supply PoE output power allocation, off& af & at
스위치 용량	128Gbps
Flash memory	256M Byte
DDRIII capacity	1G Byte
버퍼 메모리	16M
MAC	32K
정보 프레임	12K
입력전압	AC input : 100-240V 50-60HZ
소비전력	POE full load <430W
Operation TEMP / Humidity	0 ~ +50°C, 10%~90% RH Non condensing
Storage TEMP / Humidity	-40 ~ +70°C, 10%~90% RH Non condensing
치수 ( L x H x D mm)	440X319X43.6 mm
설치	1U 19 inch rack mount