

- 개요 24 * 10/100/1000Base-T ports (Data)
+ 2 * 1G SFP ports (Data)



- 특징 광 포트 25-26번 포트 : 1G 지원
AC input : 100~240V, 50~60Hz
-10 ~ +50°C operation temperature
Support 250M (long reach) / CAT6

제품사양

고정포트	24 * 10/100/1000Base-T ports (Data), 2 * 1G uplink SFP slot ports (Data), AC input : 100~240V 50~60Hz
이더넷 포트	Port 1-24 support 10/100/1000Base-T, auto-sensing, Full/half duplex MDI/MDI-X self-adaption Port 1-8 supports QoS Data Priority Default : Normal mode, all interfaces can communicate with each other, transmission Extend : Link extension mode, 17-24 ports forced 10M, link 250meter Long reach is supported when using CAT6 cable
트위스트 프로토콜	10BASE-T : Cat3, 4, 5 UTP(≤100 meter), 100BASE-TX : Cat5 or later UTP(≤100 meter) 1000BASE-T : Cat5e or later UTP(≤100 meter)
스위치 용량	52Gbps
버퍼 메모리	4M
쓰루풋	38.68Mpps
MAC	8K
입력전압	AC input : 100~240V 50~60Hz
Operation TEMP / Humidity	-10 ~ +50°C, 10%~90% RH Non condensing
Storage TEMP / Humidity	-40 ~ +70°C, 5%~95% RH Non condensing
치수 (L x H x D mm)	440x204x44 mm
설치	1U 19 inch rack mount