



- **개요** 8 \* 10/100/1000Base-T PoE ports (Power/Data)  
+ 2 \* 10/100/1000Base-T ports (Data)  
+ 2 \* 1G SFP ports (Data)
  
- **특징** 광 포트 11-12번 포트 : 1G 지원  
AC input : 100~240V, 50~60Hz  
-10 ~ +50°C operation temperature

## 제품사양

고정포트	8 * 10/100/1000Base-T PoE ports (Power/Data), 2 * 10/100/1000Base-T port(Data), 2 * 1G SFP uplink ports (Data), AC input : 100~240V 50~60Hz
이더넷 포트	Port 1-10 support 10/100/1000Base-T, auto-sensing, Full/half duplex MDI/MDI-X self-adaption
트위스트 프로토콜	10BASE-T : Cat3, 4, 5 UTP(≤100 meter), 100BASE-TX : Cat5 or later UTP(≤100 meter) 1000BASE-T : Cat5e or later UTP(≤100 meter)
POE 포트	Port 1 to port 8 DIP switch,1-8 ports support IEEE 802.3af/at
PoE Management	PoE working status, Delay start of power supply, PoE output priority configuration Scheduling of PoE operation and time, Total power limit of PoE power supply PoE output power allocation, off& af & at
스위치 용량	24Gbps
버퍼 메모리	2M
쓰루풋	8.93Mpps
MAC	2K
입력전압	AC input : 100~240V 50~60Hz
소비전력	POE full load <120W
Operation TEMP / Humidity	-20 ~ +55°C, 5%~90% RH Non condensing
Storage TEMP / Humidity	-40 ~ +75°C, 5%~95% RH Non condensing
치수 ( L x H x D mm)	202x140x45 mm
설치	Desktop