

- **개요** 16 * 10/100/1000Base-T PoE ports (Power/Data)
+ 2 * 1G SFP ports (Data)



- **특징** 광 포트 17-18번 포트 : 1G 지원
AC input : 100~240V, 50~60Hz
-10 ~ +50°C operation temperature
Support 250M (long reach) / CAT6

제품사양

고정포트	16 * 10/100/1000Base-T PoE ports (Power/Data), 2 * 1G SFP uplink ports (Data), AC input : 100~240V 50~60Hz
이더넷 포트	Port 1-16 support 10/100/1000Base-T, auto-sensing, Full/half duplex MDI/MDI-X self-adaption VLAN : Isolation mode, 1-14 ports isolated from each other, communication with 15-18 ports Default : Normal mode, all interfaces can communicate with each other, transmission Extend : Link extension mode, 8-16 ports forced 10M, link 250meter (with PoE watchdog enabled) Long reach is supported when using CAT6 cable
트위스트 프로토콜	10BASE-T : Cat3, 4, 5 UTP(≤100 meter), 100BASE-TX : Cat5 or later UTP(≤100 meter) 1000BASE-T : Cat5e or later UTP(≤100 meter)
POE 포트	Port 1 to port 16
PoE Management	PoE working status, Delay start of power supply, PoE output priority configuration Scheduling of PoE operation and time, Total power limit of PoE power supply PoE output power allocation, off& af & at
스위치 용량	36Gbps
버퍼 메모리	4M
쓰루풋	26.784Mpps
MAC	8K
입력전압	AC input : 100~240V 50~60Hz
소비전력	POE full load <150W 220 V~, 60 Hz, 2.3A (O/P:52 Vdc, each port Max 30 W, Total Max. 150 W for 16 ports)
Operation TEMP / Humidity	-10 ~ +50°C, 10%~90% RH Non condensing
Storage TEMP / Humidity	-40 ~ +70°C, 5%~95% RH Non condensing
치수 (L x H x D mm)	440x204x44 mm
설치	1U 19 inch rack mount