

- 개요 24 * 10/100/1000Base-T PoE ports (Power/Data)
+ 4 * 10G SFP+ Slot (Data)



- 특징 광 포트 25-28포트 : 10G 지원
AC input : 100-240V 50-60HZ
0 ~ +60°C operation temperature

제품사양

고정포트	24 * 10/100/1000Base-T PoE ports (Power/Data), 4 * 10G uplink SFP+ slot ports (Data), 1 * RJ45 Console port, 1 * USB port AC input : 100-240V 50-60HZ
이더넷 포트	Port 1-24 support 10/100/1000Base-T, auto-sensing, Full/half duplex MDI/MDI-X self-adaption
트위스트 프로토콜	10BASE-T : Cat3, 4, 5 UTP(≤100 meter), 100BASE-TX : Cat5 or later UTP(≤100 meter) 1000BASE-T : Cat5e or later UTP(≤100 meter)
POE 포트	Port 1 to port 24
PoE Management	PoE working status, Delay start of power supply, PoE output priority configuration Scheduling of PoE operation and time, Total power limit of PoE power supply PoE output power allocation, off& af & at
스위치 용량	128Gbps
버퍼 메모리	95.23M
RAM	128MB
MAC	16K
입력전압	AC input : 100-240V 50-60HZ
소비전력	POE full load <400W
Operation TEMP / Humidity	0 ~ +60°C, 10%~90% RH Non condensing
Storage TEMP / Humidity	-40 ~ +70°C, 10%~90% RH Non condensing
치수 (L x H x D mm)	440X280X44 mm
설치	1U 19 inch rack mount